

ADSL Wireless 11g Router



AWgR/2

- ❖ Integrated Wireless (802.11g) Access Point ITU-T G.992.1 (Annex A and Annex B / ETSI / U-R2) IEEE 802.11g and 802.11b (2.4GHz)
-

Features

- Support 54Mbps Wireless data rate
- Compatibility with IEEE 802.11g and 802.11b (2.4GHz) standards
- Wireless security with up to 128-bit WEP encryption
- All Ethernet ports support auto-crossover (MDI/MDI-X) - No need for crossover cables
- Compliant with IEEE 802.3 and IEEE 802.3u 10/100 Mbps
- Share your ADSL Internet access on your wireless and Ethernet Networks
- DMZ and Virtual Server function
- Provided operating modes include routing, bridge, static IP, PPPoE, PPPoA etc

ADSL Wireless 11g Router

Specifications

ADSL Features

- Compatible with all leading DSLAMs
- Supports DMT modulation and demodulation
- Support ITU-T G.992.1 G.992.3, G.992.4, G.992.5 Annex A
- ETSI TS 101 388 / DTS TM-06006 for Annex B
- Supports ITU-T G.992.1 (G.dmt) Annex B – Deutsch Telecom / U-R2 for Annex B (U-R2)
- G.992.1 (G.dmt) : Downstream and upstream data rates up to 8Mbps and 1Mbps
- G.992.2 (G.Lite) : Downstream and upstream data rates up to 1.5Mbps and 512Kbps
- G.992.3 / G.992.4 (ADSL2) : Downstream and upstream data rates up to 12Mbps and 1Mbps
- G.992.5 (ADSL2+) : Downstream and upstream data rates up to 24Mbps and 2Mbps

ATM Features

- WAN Mode Support : PPP Over ATM (RFC2364) and PPP Over Ethernet (RFC2516)
- LAN Mode Support : Routed / Bridge Ethernet Over ATM (RFC-2684)
- Classical Internet Protocol Over ATM (RFC-1577)
- Support ATM SAR, ATM AAL5, ATM Forum UNI3.1 / 4.0 PVC

Wireless Features

- Support IEEE 802.11g, 802.11b and Super-G Wireless Access Point
- Support 128-Bit and 64-Bit WEP encryption, WPA-PSK, 802.1x
- Data rate : Up to 108Mbps
- Transmit Power : 15 dBm
- Receive Sensitivity : 11Mbps : -80dBm / 54Mbps : -65dBm

Management Features

- Firmware upgrade via FTP
- Customize Web pages
- WAN and LAN side connection statistics
- Configuration of static routes and routing table
- Configuration of NAT / NAPT
- Password protected access
- Selection of Bridge or Router Mode
- PPP user ID and password
- Configuration of VCs (Virtual Circuits)

Physical Interfaces

- ADSL Modem / Router with four RJ-45 (10/100 Base-T) Ethernet port & an ADSL port
- ADSL Status, Power and switching hub LED indicators

Bridge Mode

- Ethernet to ADSL self-learning Transparent Bridging (IEEE 802.1D)
- Supports up to 128 MAC learning addresses

Router Features

- DHCP Server and Client
- NAPT (Network Address and Port Translation)
- NAT (Network Address Translation)
- ICMP (Internet Control Message Protocol)
- IGMP (Internet Group Management Protocol)
- DDNS (Dynamic Domain Name Service)

Security Features

- Password protected configuration access
- User authentication (PAP / CHAP) with PPP

Ethernet Features

- Compliant with IEEE 802.3 and 802.3u 10/100 Mbps
- All Ethernet ports support auto-crossover (MDI/MDI-X)

Temperature

- 32~122°F (0 ~50°C)

Humidity

- Max. 95% (Non-Condensing)

Regulatory Approvals

- FCC, CE

Application:

